



Ihr Partner für SMD -Technologie

PAGGEN Werkzeugtechnik GmbH
 Söckinger Straße 12
 D-82319 Starnberg
 Tel. 08151-16190
 info@paggen.de
 www.paggen.de



General Purpose Dust Remover - EU

- Cleans dust & grit from keyboards, optics, machinery and circuitry
- Nonflammable
- High-pressure
- High-purity, leaves no residue
- Highly economical

Product Information

General Purpose Dust Remover is a high purity electronics-grade cleaner that delivers a dry blast of inert gas to hard to reach surfaces. Use to remove dust, particles, and moisture from any surface.

Clean hard-to-reach areas like keyboards or pin connectors. Use to quickly pre-clean surfaces by removing layers of loose grime and dust before using a solvent cleaner. Also, use to remove slow-drying solvents from under surface mount components or on circuit boards, connectors or optics. There are literally hundreds of uses.

The trigger spray allows easy single-handed operation. Plastic-safe, nonflammable and leaves no residue.

Technical Details and Cleaning Data	
Chemical Family	HFO
Evaporation Rate	Instant
Moisture Content	<10 ppm
Odour	Slight, Ether
Vapor Pressure at 20°C	61.9 PSIA
Health, Safety and Environmental Data	
Flammable	No
Flashpoint	None
Organic Content (g/L)	0
RoHS, WEEE and REACH Compliant	Yes
Toxicity Rating (ppm, 8hr. TWA, TLV)	800
Packaging	
Aerosol - 231 mL	MCC-DST107
TriggerGrip™ Compatible	No
Aerosol Packaging	12 cans / box
Shelf Life	Unlimited
Recycle	

*Contact MicroCare for specific details

AVAILABILITY: Stocked by MicroCare distributors world-wide. Contact MicroCare for a distributor near you. For more information contact MicroCare directly or visit www.MicroCare.com.

Discover Perfectly Clean www.MicroCare.com

MicroCare Europe BVBA

Vekestraat 29 B11
 Industriezone 't Sas
 1910 Kampenhout, Belgium
 Tel: +32 2 251 95 05
 Email: EuroSales@MicroCare.com



Ihr Partner für SMD-Technologie

Paggen Werkzeugtechnik GmbH
 Söckinger Straße 12 82319 Starnberg
 Tel. +49-8151-16190 Fax. - 28554
www.paggen.de info@paggen.de

Zertifiziert nach
 DIN EN ISO 9001:2008